





- has more than 30 years experience
  delivers reliable IT solutions for demanding environments
  builds compact and high performance solutions
  focuses on long duration, 24/7-operation, and ruggedness
  is ISO 9001:2015-certified

- is known for providing the best assistance and services in all phases.

#### Highlights

All-in-one stainless steel HMI with integrated touch or membrane keyboard for operation in cleanroom. Very easy to clean and disinfect due to smooth sides, rounded edges and a flat, smooth front. Crafted from AISI 316L stainless steel withstanding all known cleaning agents and disinfectants.



Both the display and the keyboard are based on cutting-edge technology that works with gloves. A typical use case would be three layers of gloves, one layer of cotton gloves and two layers of nitrile/latex or silicone gloves. It is also possible to combine with thicker safety gloves. The multi touch display provides auto calibration for seamless operation.

If you choose touch keyboard, the sensitivity is adjustable to suit the number of layers of gloves. This unique technology is chosen by most of the leading pharmaceutical manufacturers, because traditional keyboards break down and cannot be cleaned completely thus compromising regulatory requirements.

Blue Line's HMIs are designed for 24/7 operation, with a low power consumption, passive cooling and without moving parts for maximum operational reliability.

Available as monitor or with integrated PC, thin client or KVM. Blue Line's modular design makes it possible to configure fully to specific requirements to functionality, finish and environment.

Blue Line's modular design makes it possible to configure to specific needs in functionality, finish and environment. Get free advice from our experts and let us set up a Teams meeting for an online demo and Q&A. Benefit from our experience and knowledge based on numerous installations in biotech and pharmaceutical sites around the world.

- Life Science / GMP / FDA environment
- Stainless steel AISI 316L
- Integrated touch or membrane keyboard
- Easy to clean & disinfect
- Withstands all known detergents: iso-propyl alcohol, non-deionized water, VHP, Spor-Klenz<sup>™</sup>, Klercide, Actisan, LpH®, Vesphene® and more
- Meets all cleanroom, GMP and FDA requirements
- 19" PCAP multi touch display
- Operable with up to 3 layers of cleanroom gloves
- IP65 dust and waterproof
- Monitor
- Display resolution 1280 x 1024
- Option for KVM extender
- · Option for integration of customers client
- Fanless operation
- · Wide range of options: USB, COM, reset and barcode reader
- Wall mount
- Long product life cycle
- · Customisation according to your requirements



- has more than 30 years experience
- delivers reliable IT solutions for demanding environments
- builds compact and high performance solutions
   focuses on long duration, 24/7-operation, and ruggedness
- is ISO 9001:2015-certified
- is known for providing the best assistance and services in all phases.

#### **Specifications**

**Model Type** 

HMI stainless steel Monitor with integrated keyboard

Construction

Fully sealed enclosure in stainless steel AISI 304 Optional acid resistant stainless steel AISI 316L

Cooling

**Fanless** 

**Ingress Protection** 

IP65

**Environment** 

Operating 0°C to +50°C

temperature

Storage -30°C to +70°C

temperature

Humidity 10 to 90% @ 40°C, non-condensing

Certification

CE / FCC CLASS A

**Display** 

19" 1280 x 1024, 5:4, SXGA TFT LCD

**Touch** 

Projected capacitive multi touch (supports gloves)

**Brightness** 

300 nits

**Viewing Angle** 

160/160

Keyboard

Touch keyboard

103 keys

Flat glass capacitive touch surface (supports

gloves)

Capacitive touchpad Numeric keypad

DIN 42115 chemical resistance Various language layouts available

Membrane keyboard

105 keys

Robust polyester front foil with key

embossment

Capacitive touchpad

Chemical, abrasion and scratch resistant

frontsheet

Various language layouts available

**Front Input / Output** 

Option for: USB 2.0 ports

COM ports Reset

All connectors come with waterproof cap

**Rear Input / Output** 

1 x HDMI / optional 1 x VGA

1 to 4 x USB 2.0 ports

1 x Power input

COM ports optional

All connectors come with waterproof cap

**Power Supply** 

+90V to +264V AC-input

Option for +10 to +36V DC-input

**Power Consumption** 

Max 40W

**Mounting** 

Wall mount

**Dimension and Weight** 

19" H 550 x W 566.2 x D 300mm

22kg

Special Function	
Option for internal barcode reader	
Warranty and After Sales Support	
Standard 1 year (option for 3 years)	

**Ordering Information** 

105x