

High Pressure IP69K Waterproof HMI Monitor 7900 Series



Highlights

Elegant and waterproof stainless steel IP69K Monitor developed for industries with extensive cleaning and spray down. Very easy to clean and disinfect due to smooth sides, rounded edges and a narrow front bezel. Designed with special hygienic bolts on rear case enabling the market's fastest and most complete cleaning.

Designed for 24/7 operation, with low power consumption, passive cooling and without moving parts for maximum operational reliability. Screen sizes in 15.6" or 21.5" with auto-calibrated touch technology for seamless operation, even with gloves.

The rear side of the waterproof IP69K HMI supports tube and swivel arm mounting with internal cable wiring providing the market's best long term protection against high pressure water treatment.

Benefit from our experience from numerous installations around the world. Let us prepare a proposal that ensures the best functionality, ergonomics and occupies as little space as possible, such as integration with food processing equipment.

Reduce cost and time spending with our global partner model based on your specific requirements. Let Blue Line take responsibility for delivery on time. Blue Line's ultimate goal is to help our customers get peace of mind by handling all relevant details such as securing the right configuration, software setup, mounting, packaging, labeling etc. Ask for references from your industry.



- Waterproof HMI Monitor for Food / Life Science / Chemical
- IP69K high pressure waterproof
- Stainless steel AISI 304 / 316L
- 15.6" or 21.5" PCAP multi touch display
- Up to full HD resolution 1920 x 1080
- True flat and ultra slim front frame design
- Fanless operation
- Optional tube mount and swivel arm with hidden connectors and cables

High Pressure IP69K Waterproof HMI Monitor 7900 Series

Specifications

Model Type

HMI stainless steel Monitor

Construction

Fully sealed enclosure in stainless steel AISI 304
Optional acid resistant stainless steel AISI 316L

Cooling

Fanless

Ingress Protection

IP66/IP69K

Environment

Operating temperature 0°C to +50°C
Option for wide temperature -20°C to +60°C
Storage temperature -30°C to +70°C
Humidity 10 to 90% @ +40°C (non-condensing)

Certification

CE / FCC CLASS A

Display

15.6"	1366 x 768, 16:9, HD (option for FHD)	color TFT LCD
21.5"	1920 x 1080, 16:9, FHD	color TFT LCD

Touch

Projected capacitive multi touch (supports gloves)*
Resistive touch (optional)
Optical bonding (optional)
*Supports 7H anti-scratch surface

Brightness

15.6"	400 nits
21.5"	250 nits
All sizes	Option for high brightness 1000 nits

Colors

16.7M / 16.2M

Viewing Angle

15.6"	160/160 - 170/170
21.5"	178/178

Rear Input / Output

1 x M12 12-pin for VGA with waterproof cover
1 x M12 17-pin for HDMI with waterproof cover
1 x M12 8-pin for USB Touch with waterproof cover
1 x M12 3-pin for DC power with waterproof cover
OSD on the rear side
Option for 1 x 2W IP65 speaker

Power Supply

+9V to +36V DC-input

Power Consumption

Max 14.7W

Mounting

VESA 100

Dimension and Weight

15.6"	H 225 x W 404.4 x D 64.5mm	4.85kg
21.5"	H 332.4 x W 540.4 x D 61.5mm	7.6kg

Accessories Included

AC to DC power adapter with M12
VGA cable with M12

Accessories Optional

Stainless steel table stand
Stainless steel wall mount with tilt
Stainless steel tube mount
Stainless steel swing arm
IP65 waterproof power adapter AC input +90 to +305V, DC output +24V, 60W, power cord type G (EU type) or B (US type)
HDMI Cable with cap L:2.0M
USB Cable with cap L:2.0M



High Pressure IP69K Waterproof HMI Monitor 7900 Series

Warranty and After Sales Support

Standard 1 year (option for 3 years)



BLUE LINE
IT for Demanding Environments

Blue Line A/S | Rho 8 | 8382 Hinnerup, Denmark
T +45 8678 5000 | www.blue-line.dk